



Handcrafted Wood Floors

Product data sheet

Craftwork Collection - Herringbone 90°

Product information

Wood type	European oak
Construction	Duo plank / Top layer Oak, bottom layer plywood
Grading	Rustic ABCD
Bevels	4-sided (long sides)
Joint	Tongue and Groove connection
Surface structure	Brushed / Rough
Colours	Available in 10 colours. See our website for a current range
Finishing	Hardwaxoil

Dimensions and packaging information

Dimension Herringbone 90° Ca.	140x700 mm
Thickness Ca. *	15/3,2 mm
* The thickness may be slightly less for roughed/planed or saw-cut boards.	
Packing unit	140x700 mm = 6 pieces = 0,588 m ² per pack
Packing information	Left and right parts packed separately. Rounding order quantity to 2 packs
Weight	Approx. 11 kg p/m ²

Installation and use

Usage	Commercial, Hospitality, Retail
Installation method	Floating installation or full gluing
Underfloor heating suitable	Yes
Underfloor cooling suitable	Yes
Resandable	Yes, but depending on original aging, it may partially/completely disappear.

Technical information

Moisture content:	On delivery approx. 8% (± 2%)
Thermal resistance:	$R = \frac{d}{\lambda} : 0,098$
Humidity:	Between 50 - 65% at a room temperature of 21°